

CLAIMS

5 1. An adjustable harp for use with a lamp having a base and a harp bracket having oppositely disposed harp mounting arms, the adjustable harp comprising,
a top member; and

10 two oppositely disposed legs depending from said top member which are adapted to be coupled to the harp mounting arms, each said leg having a first portion, a second portion telescopically received within said first portion, and locking means for locking the position of said first portion relative to said second portion,

15 whereby the height of the adjustable harp may be varied by moving the first portion relative to the second portion and subsequently locking their position through the locking means.

20 2. The adjustable harp of claim 1 wherein said locking means comprises a threaded splayed end upon said first portion and a threaded cap configured to mate with said threaded splayed end, whereby the threading of the cap upon the threaded end causes the compression of the splayed end.

25 3. The adjustable harp of claim 1 wherein said locking means comprises said first portion having a threaded end, a threaded cap configured to mate with said threaded end, and resilient material positioned between said end and said cap, whereby the threading of the cap upon the end causes the resilient material to expand and
30 frictionally contact the second portion.

4. A lamp adjustable harp comprising,
a top member extending to two oppositely disposed
legs, each said leg includes a first portion, a second
portion telescopically received within said first portion,
5 and locking means for locking the position of said first
portion relative to said second portion along a range of
positions between a telescopically retracted position and
a telescopically extended position,

whereby the height of the adjustable harp may be
10 varied by telescopically moving the second portion into the
first portion and then locking them relative to each other.

5. The adjustable harp of claim 4 wherein said
locking means comprises a threaded splayed end upon said
15 first portion and a threaded cap configured to mate with
said threaded splayed end, whereby the threading of the cap
upon the threaded end causes the compression of the splayed
end.

6. The adjustable harp of claim 4 wherein said
locking means comprises said first portion having a
20 threaded end, a threaded cap configured to mate with said
threaded end, and resilient material positioned between
said end and said cap, whereby the threading of the cap
25 upon the end causes the resilient material to expand and
frictionally contact the second portion.